

S80 HIGH ENERGY SCREENER

The S80 is designed for users who require less capacity than the S130 and S190 models offer, but who are not willing to sacrifice the quality features found on the McCloskey S-Range, such as the High Energy Screenbox, large hopper and large engine bay.

Users with smaller floats or in areas with strict transport regulations will benefit from the smaller transport dimensions.

The S80 can employ the steepest screen angle of any three-way-split screening plant currently available, ensuring best-in-class screening ability in materials like sand and peastone.



Screenbox
4.5' x 10' High Energy Screenbox offers class-leading screening in materials like sand and peastone.



Hopper
7.85 yd³ (6 m³) hopper is able to work directly with large excavators and has steep sides for maximum efficiency.



Large Open Engine Bay
Provides ample access for servicing and maintaining the power unit and hydraulics.



36" Chevron Main Conveyor
Prevents rollback of material while operating at steep screenbox angles.



Transport Size
Compact transportation size is perfect for contractors looking for highly portable mobile screening.



085	Engine: 84 hp (63 kw) Diesel	S80 HIGH ENERGY SCREENER
	Transport Height: 10' 6" (3.2m)	
	Transport Length: 44' 4" (13.21m)	
	Transport Width: 8' 4" (2.5m)	
	Stockpile Height: 12' 5" (3790mm)	
Weight: 44,092 lbs (20,000 kg) estimated		

www.mccloskeyinternational.com

McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate – McCloskey International assumes no liability resulting from errors or omissions in this document.